



XP
XTREMEPRO™



Extreme work calls for extreme tools, and the FinishPro 41XP is up to the challenge! With a variety of features designed to make any job easier, the FinishPro 41XP is ideal for the most demanding Pro.

Applications:

Interior trim, exterior trim, crown molding, base molding, door and window casings, cabinets, chair rails, hardwood flooring

FinishPro® 41 Features and Benefits:


- Two-year limited warranty
- Adjustable depth-of-drive
- NeverLube® technology – no lubrication required
- Easy-clear latch – to clear jams fast
- No-mar pads with onboard storage to protect work materials
- Magnesium housing - lightweight and comfortable to use all day
- Comfort and convenience features include: overmold comfort grip, overmold trigger, 360° adjustable exhaust
- Construction ruler – for quick measurements
- Advanced belt hook – convenient storage


Specifications:

Item#: 1Z0001N Sequential Actuation (Restrictive)
Tool Weight: 4 lbs (3.6 kg)
Height: 11-5/8" (249 mm)
Length: 13" (330 mm)
Nail Capacity: 100
Reg. Operating Pressure: 70-120 psig
Mode of Operation: Tool is available with either contact actuation or sequential trigger mechanism
Hose Fitting: 1/4" NPT

Fastener Specifications:

Gauge: 15
Fastener Range: 1-1/4" – 2-1/2"
Finish: Bright Basic/Galvanized nails





Choose the right trigger system for your specific needs!

Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how Senco will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596 to find your nearest Authorized Senco Dealer, Distributor or visit our web site at: www.senco.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>