

General Description

Featuring high maximum SPL and excellent transient response, the cardioid e 903 is suitable for a wide range of instruments, and an ideal choice for miking snare drums.



Technical Data

Pick-up pattern	cardioid
Frequency response	40 – 16,000 Hz
Sensitivity	
(free field, no load, 1 kHz)	2.8 mV/Pa at 1 kHz =
	51 dB (0 dB = 1V/Pa)
Nominal impedance	350 Ω
Min. terminating impedance	1 kΩ
Dimensions	41 x 176 mm
Weight	320 g

Features

- Rugged metal body
- Advanced shock-mount design for excellent suppression of handling noise
- Consistent on-/off-axis response
- Hum compensating coil
- Delivery includes a pouch and a microphone clamp

Profile

Cardioid instrument microphone, hum compensating coil, frequency response 40 – 16,000 Hz, sensitivity (free field, no load) 2,8 mV/Pa at 1 kHz = 51 dB (0 dB = 1V/Pa), nominal impedance 350 Ω, min. terminating impedance 1 kΩ, dimensions 41 x 176 mm, weight 320 g.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>