



## ZKI245

6kg washer dryer



### Laundry Features

- 6kg Load
- Jetsystem Advanced Technology
- Delay start
- Quick wash
- Turbody plus
- LED display and electronic controls
- 24+ programmes
- 1400rpm spin speed
- Automatic half load
- Wash Programmes include: Easy Iron, Handwash, Mini 30°, Cottons, Cottons Economy, Synthetics, Delicates, Rinse, Drain, Spin

### Options to tailor Programmes

- Quick wash
- Variable spin speed including rinse hold
- Prewash
- Extra rinse
- Daily wash
- Easy ironing

### Drying Programmes

- Drying load 3kg
- Drying timer

### Energy

Energy Rating

**B**

Washing

**A**

## TURBODRY PLUS

A unique drying circuit where heat is directed into the wash load by a fan. Moisture created through the drying process is channelled through a cleverly designed condenser. This gives faster drying times, reduced energy and water consumptions, with no need to vent!

# SPECIFICATION TABLES



# COOKING

## SINGLE OVENS

| MODEL   | ZB6504X    | ZB6904X  | ZB6504N<br>ZB6504X | ZB6514X  | ZB6330W<br>ZB6330X | ZB6330W<br>ZB6330X | ZB6150X  | ZB6560W<br>ZB6560X | ZB6900X     |
|---|------------|----------|--------------------|----------|--------------------|--------------------|----------|--------------------|-------------|
| <b>OVEN FUNCTIONS (t=top, m=main)</b>               |            |          |                    |          |                    |                    |          |                    |             |
| Thermaflow® fan operated cooking                    | ■          | ■        | ■                  | ■        | ■                  | ■                  |          | ■                  | ■           |
| Fan assisted cooking                                |            |          |                    |          |                    |                    |          |                    | ■           |
| Thermal grilling                                    | ■          | ■        | ■                  | ■        |                    |                    |          | ■                  | ■           |
| Conventional cooking                                | ■          | ■        | ■                  |          |                    |                    | ■        |                    | ■           |
| Pizza setting                                       | ■          | ■        |                    |          |                    |                    |          |                    |             |
| Booster   | ■          | ■        |                    |          |                    |                    |          |                    |             |
| Fan controlled defrosting                           | ■          | ■        | ■                  | ■        | ■                  | ■                  |          | ■                  | ■           |
| Full width grill                                    | ■          | ■        | ■                  | ■        |                    |                    | ■        | ■                  | ■           |
| Economy grill                                       | ■          | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| Bottom heat - reheat                                | ■          | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| Top heat browning                                   | ■          | ■        | ■                  |          |                    |                    | ■        |                    | ■           |
| <b>OVEN FEATURES</b>                                |            |          |                    |          |                    |                    |          |                    |             |
| Oven door(s) (Q=quadruple T=triple, D=double)       | Q          | T        | D                  | D        | D                  | D                  | D        | D                  | T           |
| Interior lights                                     | 1x15       | 1x15     | 1x15               | 1x15     | 1x15               | 1x15               | 1x15     | 1x15               | 2x15        |
| Interior lights                                     | Side       | Side     | Side               | Side     | Side               | Side               | Side     | Side               | 1 Each Side |
| Digital push button controls                        | ■          | ■        |                    | ■        |                    |                    |          |                    |             |
| Retractable controls                                |            |          | ■                  | ■        |                    |                    |          |                    |             |
| Rotary controls                                     |            |          |                    |          | ■                  | ■                  | ■        | ■                  | ■           |
| Controls behind glass                               | ■          | ■        | ■                  |          |                    |                    |          |                    |             |
| Digital display                                     | ■          | ■        |                    |          |                    |                    |          |                    |             |
| Digital temperature control                         | ■          | ■        |                    |          |                    |                    |          |                    |             |
| Compact hinge                                       | ■          | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| Cooling fan   | ■          | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| Easy installation - side handles and stability feet | ■          | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| <b>PROGRAMMER</b>                                   |            |          |                    |          |                    |                    |          |                    |             |
| Mechanical minute minder                            |            |          |                    |          |                    | ■                  |          |                    |             |
| Fully programmable electronic clock & minute minder |            |          | ■                  | ■        | ■                  |                    |          | ■                  | ■           |
| Digital controls with menu guided cooking           | ■          | ■        |                    |          |                    |                    |          |                    |             |
| <b>CLEANING</b>                                     |            |          |                    |          |                    |                    |          |                    |             |
| Pyrolytic oven cleaning 2)                          | ■          |          |                    |          |                    |                    |          |                    |             |
| Catalytic lining / liners                           |            | ■        | ■                  | ■        |                    |                    |          | ■                  | ■           |
| Easy clean enamel interior                          |            |          |                    |          | ■                  | ■                  | ■        |                    |             |
| Fold down grill                                     |            | ■        | ■                  | ■        |                    |                    |          | ■                  |             |
| <b>EQUIPMENT SUPPLIED</b>                           |            |          |                    |          |                    |                    |          |                    |             |
| Telescopic runners                                  | Optional   | Optional | Optional           | Optional |                    |                    |          |                    |             |
| Chrome grid runners                                 | ■          | ■        | ■                  | ■        |                    |                    |          | ■                  | ■           |
| Chrome auto-stop non-tip shelves                    | 2          | 2        | 2                  | 2        | 2                  | 2                  | 2        | 2                  | 1           |
| Grill pan, trivet & handle(s)                       | ■          | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| <b>INTERNAL OVEN DIM. (t=top, m=main)</b>           |            |          |                    |          |                    |                    |          |                    |             |
| Volume (usage)                                      | Litres     | 53       | 53                 | 53       | 53                 | 53                 | 53       | 53                 | 67          |
| Height  | mm         | 335      | 335                | 335      | 335                | 335                | 335      | 335                | 316         |
| Width   | mm         | 395      | 395                | 395      | 395                | 405                | 405      | 395                | 555         |
| Depth   | mm         | 400      | 400                | 400      | 400                | 400                | 410      | 400                | 381         |
| <b>ENERGY INFORMATION</b>                           |            |          |                    |          |                    |                    |          |                    |             |
| Oven temperature range                              | °C         | 30-250   | 30-250             | 50-250   | 50-250             | 50-250             | 50-250   | 50-250             | 50-250      |
| Energy class  |            | A        | A                  | A        | A                  | A                  | A        | A                  | A           |
| Energy efficiency class in mode                     | Static/Fan | F        | F                  | F        | F                  | F                  | S        | F                  | F           |
| Cooktime standard load static                       | Minutes    | 43       | 43                 | 43       | 43                 | 43                 | 43       | 43                 | 46          |
| Cooktime standard load fan                          | Minutes    | 41       | 41                 | 41       | 41                 | 41                 | N/A      | 41                 | 50          |
| Energy consumption static                           | kW/h       | 0.79     | 0.79               | 0.79     | 0.79               | 0.79               | 0.79     | 0.79               | 1.12        |
| Energy consumption fan                              | kW/h       | 0.78     | 0.78               | 0.78     | 0.78               | 0.78               | N/A      | 0.78               | 0.99        |
| Standby power                                       | W          | 1.3      | 1                  | 1        | 1.3                | 1                  | 0        | 1                  | 1           |
| <b>ELECTRICAL CONNECTION</b>                        |            |          |                    |          |                    |                    |          |                    |             |
| Connected load                                      | kW         | 2.5      | 2.5                | 2.5      | 2.1                | 2.1                | 2.1      | 2.5                | 2.9         |
| Fuse rating   | A          | 13       | 13                 | 13       | 13                 | 13                 | 13       | 13                 | 13          |
| Oven/Grill power (max)                              | kW         | 2.5/2.45 | 2.5/2.45           | 2.5/2.45 | 2.1/2.45           | 2.1/1.65           | 2.1/1.65 | 2.5/2.45           | 2.9/2.8     |
| <b>SAFETY AND INTERFERENCE SUPPRESSION</b>          |            |          |                    |          |                    |                    |          |                    |             |
| Low Voltage Directive (LVD)                         |            | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| Electromagnetic Compatibility (EMC)                 |            | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| <b>LITERATURE SUPPLIED</b>                          |            |          |                    |          |                    |                    |          |                    |             |
| Operation and installation instructions             |            | ■        | ■                  | ■        | ■                  | ■                  | ■        | ■                  | ■           |
| <b>APPLIANCE DIMENSIONS</b>                         |            |          |                    |          |                    |                    |          |                    |             |
| Height  | mm         | 590      | 590                | 590      | 590                | 590                | 590      | 590                | 474         |
| Width   | mm         | 594      | 594                | 594      | 594                | 594                | 594      | 594                | 894         |
| Depth   | mm         | 560      | 560                | 560      | 560                | 560                | 560      | 560                | 545         |
| Net weight  | kg         | 34.6     | 34.6               | 34.6     | 30.6               | 30.6               | 29.7     | 30                 | 47          |
| <b>APERTURE DIMENSIONS 1)</b>                       |            |          |                    |          |                    |                    |          |                    |             |
| Height*   | mm         | 593      | 593                | 593      | 593                | 593                | 593      | 593                | 460         |
| Width   | mm         | 560      | 560                | 560      | 560                | 560                | 560      | 560                | 860         |
| Depth   | mm         | 550      | 550                | 550      | 550                | 550                | 550      | 550                | 550         |
| <b>PACKAGING DIMENSIONS</b>                         |            |          |                    |          |                    |                    |          |                    |             |
| Height  | mm         | 660      | 660                | 660      | 660                | 660                | 660      | 660                | 585         |
| Width   | mm         | 630      | 630                | 630      | 630                | 630                | 630      | 630                | 980         |
| Depth   | mm         | 660      | 660                | 660      | 660                | 660                | 660      | 660                | 670         |
| Gross weight  | kg         | 36.1     | 36.1               | 36.1     | 32.1               | 32.1               | 31.2     | 31.5               | 35.7        |

1) Refer to User Instructions before cutting out. 2) Pyrolytic cleaning : 5.0kW/h. \* 593mm if built under worktop or hob for all models.

# COOKING

## DOUBLE OVENS

| MODEL   | ZD685X      | ZD650X<br>ZD650N | ZD630X<br>ZD630N | ZD6575X<br>ZD6575N | ZD630X<br>ZD630N |
|---|-------------|------------------|------------------|--------------------|------------------|
| <b>OVEN FUNCTIONS (t=top, m=main)</b>               |             |                  |                  |                    |                  |
| Thermaflow® fan operated cooking                    | ■           | ■                | ■                | ■                  | ■                |
| Fan assisted cooking                                |             |                  |                  | ■                  |                  |
| Thermal grilling                                    | ■           | ■                |                  | ■                  | ■                |
| Conventional cooking                                | ■           | ■                | ■                | ■                  | ■                |
| Pizza setting                                       | ■           |                  |                  | ■                  |                  |
| Booster   | ■           |                  |                  | ■                  |                  |
| Fan controlled defrosting                           | ■           | ■                | ■                | ■                  | ■                |
| 80° keep warm                                       | ■           |                  |                  | ■                  |                  |
| Full width grill                                    | ■           | ■                | ■                | ■                  | ■                |
| Economy grill                                       | ■           | ■                | ■                | ■                  | ■                |
| Bottom heat - reheat                                | ■           | ■                | ■                | ■                  | ■                |
| <b>OVEN FEATURES</b>                                |             |                  |                  |                    |                  |
| Oven door(s) (Q=quadruple T=triple, D=double)       | D           | D                | D                | D                  | D                |
| Interior lights                                     | 2x25        | 2x25             | 2x25             | 1x38   1x25        | 2x25             |
| Interior lights                                     | Back   Side | Back   Side      | Back   Side      | Side   Side        | Side   Side      |
| Digital touch controls                              | ■           |                  |                  |                    |                  |
| Retractable controls                                |             | ■                |                  | ■                  |                  |
| Rotary controls                                     |             |                  | ■                |                    | ■                |
| Controls behind glass                               |             | ■                |                  |                    |                  |
| Digital display                                     | ■           |                  |                  |                    |                  |
| Digital temperature control                         | ■           |                  |                  |                    |                  |
| Compact hinge                                       | ■           | ■                | ■                | ■                  | ■                |
| Cooling fan   | ■           | ■                | ■                | ■                  | ■                |
| <b>PROGRAMMER</b>                                   |             |                  |                  |                    |                  |
| Mechanical minute minder                            |             |                  |                  |                    |                  |
| Fully programmable electronic clock & minute minder |             | ■                | ■                | ■                  | ■                |
| Digital controls with menu guided cooking           | ■           | ■                |                  |                    |                  |
| <b>CLEANING</b>                                     |             |                  |                  |                    |                  |
| Catalytic lining / liners                           | ■           | ■                |                  | ■                  | ■                |
| Easy clean enamel interior                          |             |                  |                  |                    |                  |
| Fold down grill                                     |             |                  | Top              |                    |                  |
| <b>EQUIPMENT SUPPLIED</b>                           |             |                  |                  |                    |                  |
| Telescopic runners                                  | Optional    | Optional         | Optional         |                    |                  |
| Chrome grid runners                                 | ■           | ■                |                  | ■                  | ■                |
| Chrome auto-stop non-tip shelves                    | 1   2       | 1   2            | 1   2            | 1   2              | 1   2            |
| Grill pan, trivet & handle(s)                       | ■           | ■                | ■                | ■                  | ■                |
| <b>INTERNAL OVEN DIM. (t=top, m=main)</b>           |             |                  |                  |                    |                  |
| Volume (usage)                                      | Litres      | 31   53          | 31   53          | 31   57            | 35   49          |
| Height  | mm          | 180   330        | 180   330        | 180   350          | 260   270        |
| Width   | mm          | 420   420        | 420   420        | 420   420          | 345   445        |
| Depth   | mm          | 405   385        | 405   385        | 405   385          | 385   410        |
| <b>ENERGY INFORMATION</b>                           |             |                  |                  |                    |                  |
| Oven temperature range                              | °C          | 50-250           | 50-250           | 50-250             | 50-250           |
| Energy class  |             | B   B            | B   A            | B   A              | A   B            |
| Energy efficiency class in mode                     | Static/Fan  | S   F            | S   F            | S   F              | F   S            |
| Cooktime standard load static                       | Minutes     | 38   47          | 42   NA          | 40   NA            | 46   51          |
| Cooktime standard load fan                          | Minutes     | NA   52          | NA   49          | NA   47            | 42   60          |
| Energy consumption static                           | kW/h        | 0.71   0.96      | 0.74   NA        | 0.71   NA          | 0.86   0.98      |
| Energy consumption fan                              | kW/h        | NA   0.91        | NA   0.78        | NA   0.79          | 0.79   0.99      |
| Standby power                                       | W           | 1.1              | 1.1              | 1.1                | 1.1              |
| <b>ELECTRICAL CONNECTION</b>                        |             |                  |                  |                    |                  |
| Connected load                                      | kW          | 5.6              | 5.4              | 5.6                | 6.4              |
| Fuse rating   | A           | 30               | 30               | 30                 | 30               |
| Oven power (max)                                    | kW          | 1.7   3.2        | 1.7   2.5        | 1.7   2.5          | 1.7   2.5        |
| Grill power (max)                                   | kW          | 2.3   2.3        | 2.8   2.3        | 2.8   NA           | 2.8   2.3        |
| <b>SAFETY AND INTERFERENCE SUPPRESSION</b>          |             |                  |                  |                    |                  |
| Low Voltage Directive (LVD)                         |             | ■                | ■                | ■                  | ■                |
| Electromagnetic Compatibility (EMC)                 |             | ■                | ■                | ■                  | ■                |
| <b>LITERATURE SUPPLIED</b>                          |             |                  |                  |                    |                  |
| Operation and installation instructions             |             | ■                | ■                | ■                  | ■                |
| <b>APPLIANCE DIMENSIONS</b>                         |             |                  |                  |                    |                  |
| Height  | mm          | 888              | 888              | 888                | 720              |
| Width   | mm          | 595              | 595              | 595                | 593              |
| Depth   | mm          | 545              | 545              | 545                | 550              |
| Net weight  | kg          | 53               | 53               | 53                 | 50               |
| <b>APERTURE DIMENSIONS 1)</b>                       |             |                  |                  |                    |                  |
| Height*   | mm          | 872              | 872              | 872                | 870              |
| Width   | mm          | 558              | 558              | 558                | 600              |
| Depth   | mm          | 550              | 550              | 550                | 560              |
| <b>PACKAGING DIMENSIONS</b>                         |             |                  |                  |                    |                  |
| Height  | mm          | 965              | 965              | 965                | 800              |
| Width   | mm          | 665              | 665              | 665                | 660              |
| Depth   | mm          | 680              | 680              | 680                | 660              |
| Gross weight  | kg          | 55               | 55               | 55                 | 52               |

1) Refer to User Instructions before cutting out.

## COOKING

| MODEL                             | MICROWAVES                       |                   |                  |     |
|-----------------------------------|----------------------------------|-------------------|------------------|-----|
|                                   | ZNF31X                           | ZNF21X            | ZNM11N<br>ZNM11X |     |
|                                   | Combi Microwave Fan Oven & Grill | Microwave & Grill | Solo Microwave   |     |
| <b>PERFORMANCE</b>                |                                  |                   |                  |     |
| Microwave output (IEC 705)        | 1000W                            | 1000W             | 900W             |     |
| Heating category 1)               | E                                | E                 | E                |     |
| Grill output                      | 1500                             | 1500              |                  |     |
| Convection oven output            | 1600                             |                   |                  |     |
| <b>FEATURES</b>                   |                                  |                   |                  |     |
| Fully built-in                    | ■                                | ■                 | ■                |     |
| Under counter installation        | ■                                | ■                 | ■                |     |
| In-column installation            | ■                                | ■                 | ■                |     |
| Microwave power levels            | 5                                | 5                 | 5                |     |
| Hinged grill                      | ■                                | ■                 | ■                |     |
| Electronic push controls          | 5                                | 5                 | 4                |     |
| Control knobs                     | 2                                | 2                 | 1                |     |
| Electronic clock/programmer       | ■                                | ■                 | ■                |     |
| Programme end signal              | ■                                | ■                 | ■                |     |
| Internal light                    | ■                                | ■                 | ■                |     |
| Child lock                        | ■                                | ■                 | ■                |     |
| <b>COOKING MODES</b>              |                                  |                   |                  |     |
| Microwave                         | ■                                | ■                 | ■                |     |
| Grill                             | ■                                | ■                 |                  |     |
| Microwave & Grill                 | ■                                | ■                 |                  |     |
| Convection (Fan)                  | ■                                |                   |                  |     |
| Microwave & Convection            | ■                                |                   |                  |     |
| Defrost by time                   | ■                                | ■                 | ■                |     |
| Auto defrost by weight programmes | 5                                | 5                 | 4                |     |
| Auto cook by weight programmes    |                                  |                   | 8                |     |
| Quickstart                        | ■                                | ■                 | ■                |     |
| <b>TECHNICAL</b>                  |                                  |                   |                  |     |
| Total load rating                 | Kw                               | 3.4               | 2.5              | 1.3 |
| Fuse                              | A                                | 16                | 13               | 13  |
| <b>PRODUCT DIMENSIONS</b>         |                                  |                   |                  |     |
| Oven volume                       | litres                           | 38                | 38               | 26  |
| Product height                    | mm                               | 455               | 455              | 460 |
| Product width                     | mm                               | 594               | 594              | 592 |
| Product depth                     | mm                               | 542               | 542              | 437 |
| Net weight                        | Kg                               | 35                | 35               | 18  |
| <b>BUILT-IN DIMENSIONS 2)</b>     |                                  |                   |                  |     |
| Built-in height                   | mm                               | 450               | 450              | 450 |
| Built-in width                    | mm                               | 560               | 560              | 560 |
| Built-in depth                    | mm                               | 600               | 600              | 500 |
| <b>PACKAGING DIMENSIONS</b>       |                                  |                   |                  |     |
| Height                            | mm                               | 535               | 535              | 525 |
| Width                             | mm                               | 680               | 680              | 660 |
| Depth                             | mm                               | 660               | 660              | 535 |
| Gross weight                      | Kg                               | 38                | 38               | 21  |

1) Heating category of the microwave oven in line with government guidelines  
2) Installation aperture dimensions, for full details refer to installation guidelines

## COOKING

| MODEL                       | COFFEE MACHINE |                  |     |
|-----------------------------|----------------|------------------|-----|
|                             | ZCF637X        | ZDRAG00X         |     |
|                             | Coffee Machine | Accessory Drawer |     |
| <b>TECHNICAL DATA</b>       |                |                  |     |
| Connected load              | kW             | 1.07             |     |
| Fuse rating                 | A              | 13               |     |
| Lamp                        |                | 20W Halogen      |     |
| Working pressure            |                | 12               |     |
| <b>PRODUCT DIMENSIONS</b>   |                |                  |     |
| Product height              | mm             | 357              | 95  |
| Product width               | mm             | 594              | 594 |
| Product depth               | mm             | 260              | 465 |
| Net weight                  | kg             | 17.6             | 6.8 |
| <b>BUILT-IN DIMENSIONS</b>  |                |                  |     |
| Built-in height             | mm             | 450              | 450 |
| Built-in width              | mm             | 563              | 563 |
| Built-in depth              | mm             | 600              | 600 |
| <b>PACKAGING DIMENSIONS</b> |                |                  |     |
| Height                      | mm             | 425              | 130 |
| Width                       | mm             | 663              | 640 |
| Depth                       | mm             | 338              | 535 |
| Gross weight                | kg             | 19.0             | 8.0 |

## COOKING

| MODEL                                      | GAS HOBBS  |            |            |                        |            |              |                      |            |                      |                    |            |            |
|--|------------|------------|------------|------------------------|------------|--------------|----------------------|------------|----------------------|--------------------|------------|------------|
|  | ZGS7821TX  | ZGS7821TX  | ZGS8821TX  | ZGS8821CX<br>ZGS8821CN | ZGS8821X   | ZGF7821TX    | ZGG842CX<br>ZGG842CN | ZGF842X    | ZGL821TX<br>ZGL821TW | ZGL821X<br>ZGL821W | ZGF9821X   | ZGS322TX   |
| <b>HOB FEATURES</b>                        |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Number of cooking zones                    | 5          | 5          | 4          | 4                      | 4          | 5            | 4                    | 4          | 4                    | 4                  | 5          | 2          |
| Ignition type                              | Integrated | Integrated | Integrated | Integrated             | Integrated | Integrated   | Integrated           | Integrated | Integrated           | Integrated         | Integrated | Integrated |
| Control position                           | Front      | Front      | Front      | Front                  | Front      | Front        | Side                 | Front      | Side                 | Side               | Front      | Front      |
| Control type                               | Rotary     | Rotary     | Rotary     | Rotary                 | Rotary     | Rotary       | Rotary               | Rotary     | Rotary               | Rotary             | Rotary     | Rotary     |
| Wok burner                                 | ■          | ■          | ■          | ■                      | ■          | ■            |                      |            |                      |                    | ■          |            |
| Safety thermocouples                       | ■          | ■          | ■          | ■                      | ■          | ■            |                      |            | ■                    |                    |            | ■          |
| Cast Iron pan supports                     | ■          | Matt black | ■          | ■                      | Matt black | ■            | ■                    |            |                      |                    |            |            |
| Design                                     | Flat       | Flat       | Flat       | Flat                   | Flat       | Gas on Glass | Gas on Glass         | Soft       | Soft                 | Soft               | Soft       | Domino     |
| No. of stability fingers                   | 5          | 5          | 5          | 5                      | 5          | 4            | 4                    | 4          | 8                    | 8                  | 4          | 4          |
| <b>ZONE SPECIFICATION</b>                  |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Front left spec 2)                         | SR         | SR         | SR         | SR                     | SR         | SR           | R                    | S          | R                    | R                  | S          |            |
| Front left rating 3)                       | kW         | 2.0        | 2.0        | 2.0                    | 2.0        | 2.0          | 1.9                  | 2.9        | 1.0                  | 3.0                | 3.0        | 1.0        |
| Front left diameter                        | mm         | 70         | 70         | 70                     | 70         | 70           | 70                   | 100        | 54                   | 100                | 100        | 54         |
| Front right spec 2)                        |            | S          | S          | S                      | S          | S            | S                    | R          | S                    | S                  | R          |            |
| Front right rating 3)                      | kW         | 1.0        | 1.0        | 1.0                    | 1.0        | 1.0          | 1.0                  | 3.0        | 1.0                  | 1.0                | 1.0        | 3.0        |
| Front right diameter                       | mm         | 54         | 54         | 54                     | 54         | 54           | 48                   | 54         | 100                  | 48                 | 54         | 122        |
| Rear left spec 2)                          |            | SR         | SR         | SR                     | SR         | SR           | SR                   | SR         | SR                   | SR                 | SR         | SR         |
| Rear left rating 3)                        | kW         | 2.0        | 2.0        | 2.0                    | 2.0        | 2.0          | 1.9                  | 1.9        | 2.0                  | 2.0                | 2.0        | 2.0        |
| Rear left diameter                         | mm         | 70         | 70         | 70                     | 70         | 70           | 70                   | 70         | 70                   | 70                 | 70         | 62         |
| Rear right spec 2)                         |            | R          | R          | TC                     | TC         | TC           | SR                   | SR         | SR                   | SR                 | SR         | SR         |
| Rear right rating 3)                       | kw         | 3.0        | 3.0        | 4.0                    | 4.0        | 4.0          | 1.9                  | 1.9        | 2.0                  | 2.0                | 2.0        | 2.0        |
| Rear right diameter                        | mm         | 100        | 100        | 122                    | 122        | 122          | 70                   | 70         | 70                   | 70                 | 62         |            |
| Middle front spec 2)                       |            |            |            |                        |            |              |                      |            |                      |                    |            | S          |
| Middle front rating 3)                     | kW         |            |            |                        |            |              |                      |            |                      |                    |            | 1.0        |
| Middle front diameter                      | mm         |            |            |                        |            |              |                      |            |                      |                    |            | 54         |
| Middle rear spec                           |            | TC         | TC         |                        |            |              | TC                   |            |                      |                    |            | TC         |
| Middle rear rating                         | kW         | 4.0        | 4.0        |                        |            |              | 4.0                  |            |                      |                    |            | 2.0        |
| Middle rear diameter                       | mm         | 129        | 129        |                        |            |              | 122                  |            |                      |                    |            | 122        |
| <b>ELECTRICAL CONNECTION</b>               |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Total rating (max.) 3)                     | kW         | 12         | 12         | 9                      | 9          | 9            | 9.6                  | 7.7        | 8                    | 8                  | 8          | 12         |
| Fuse rating                                | A          | 3          | 3          | 3                      | 3          | 3            | 3                    | 3          | 3                    | 3                  | 3          | 3          |
| <b>SAFETY AND INTERFERENCE SUPPRESSION</b> |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Low Voltage Directive (LVD)                |            | ■          | ■          | ■                      | ■          | ■            | ■                    | ■          | ■                    | ■                  | ■          | ■          |
| Electromagnetic Compatibility (EMC)        |            | ■          | ■          | ■                      | ■          | ■            | ■                    | ■          | ■                    | ■                  | ■          | ■          |
| Gas directive                              |            | ■          | ■          | ■                      | ■          | ■            | ■                    | ■          | ■                    | ■                  | ■          | ■          |
| <b>LITERATURE SUPPLIED</b>                 |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Operation and installation instructions    |            | ■          | ■          | ■                      | ■          | ■            | ■                    | ■          | ■                    | ■                  | ■          | ■          |
| <b>APPLIANCE DIMENSIONS</b>                |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Height (above worktop)                     | mm         | 15         | 15         | 8                      | 8          | 8            | 8                    | 8          | 15                   | 12                 | 15         | 8          |
| Width                                      | mm         | 744        | 744        | 594                    | 594        | 594          | 680                  | 580        | 580                  | 580                | 580        | 290        |
| Depth                                      | mm         | 510        | 510        | 510                    | 510        | 510          | 510                  | 510        | 510                  | 500                | 500        | 510        |
| Net weight                                 | kg         | 14.4       | 14.4       | 12.8                   | 12.8       | 12.8         | 15.4                 | 12.1       | 8.6                  | 8.4                | 8.4        | 18.3       |
| <b>APERTURE DIMENSIONS 1)</b>              |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Height                                     | mm         | 30         | 30         | 30                     | 30         | 30           | 40                   | 40         | 30                   | 30                 | 30         | 30         |
| Width                                      | mm         | 560        | 560        | 560                    | 560        | 560          | 560                  | 550        | 560                  | 550                | 550        | 830        |
| Depth                                      | mm         | 480        | 480        | 480                    | 480        | 480          | 480                  | 470        | 480                  | 470                | 470        | 480        |
| <b>PACKAGING DIMENSIONS</b>                |            |            |            |                        |            |              |                      |            |                      |                    |            |            |
| Height                                     | mm         | 100        | 160        | 150                    | 150        | 150          | 150                  | 150        | 150                  | 140                | 140        | 148        |
| Width                                      | mm         | 870        | 870        | 680                    | 680        | 680          | 790                  | 680        | 680                  | 680                | 680        | 985        |
| Depth                                      | mm         | 620        | 620        | 620                    | 620        | 620          | 630                  | 620        | 620                  | 620                | 620        | 610        |
| Gross weight                               | kg         | 15         | 15         | 13.5                   | 13.5       | 13.5         | 16.1                 | 14.7       | 9.2                  | 9                  | 9          | 19         |

1) Refer to User Instructions before cutting out  
2) S=Simmer burner; R=Rapid burner; SR=Semi-Rapid; HS=High Speed burner; TC=Triple Crown burner  
3) For gas conversion purpose 3.450 BTU = 1kW

# COOKING

| MODEL                                      | INDUCTION HOBS |           | CERAMIC HOBS |           |        | SOLID PLATE HOBS   |                        |                  |                  |
|--|----------------|-----------|--------------|-----------|--------|--------------------|------------------------|------------------|------------------|
|  | ZKT652DX       | ZXE65X    | ZKT663LX     | ZKT641H   | ZIT64X | ZVW64DX<br>ZVW64OF | ZBE603W/1<br>ZBE603Y/1 | ZEL63W<br>ZEL63X | ZDE320X          |
| <b>HOB FEATURES</b>                        |                |           |              |           |        |                    |                        |                  |                  |
| Number of cooking zones                    | 4              | 4         | 4            | 4         | 4      | 4                  | 4                      | 4                | 2                |
| Control position                           | Front          | Front     | Front        | Front     | Front  | Front              | Front                  | Side             | Front            |
| Control type                               | Touch          | Touch     | Touch        | Touch     | Touch  | Rotary             | Rotary                 | Rotary           | Rotary           |
| Residual heat/hob on indicator             | ■              | ■         | ■            | ■         | ■      | ■                  |                        |                  |                  |
| Electronic timer                           | ■              | ■         | ■            | ■         | ■      |                    |                        |                  |                  |
| Child lock                                 | ■              | ■         | ■            | ■         | ■      |                    |                        |                  |                  |
| Auto cut-off                               | ■              | ■         | ■            | ■         | ■      |                    |                        |                  |                  |
| No of booster zones                        | 2              | 1         |              |           |        |                    |                        |                  |                  |
| Automatic heat up                          |                | ■         | ■            | ■         |        |                    |                        |                  |                  |
| Pot sensors                                | ■              | ■         |              |           |        |                    |                        |                  |                  |
| <b>ZONE SPECIFICATION</b>                  |                |           |              |           |        |                    |                        |                  |                  |
| Front left spec 2)                         |                |           | F            | HA        | F      | F                  | F                      | F                |                  |
| Front left rating 3)                       | kW 2.2-3.1     | 2.2   3.1 | 0.75   2.2   | 2.4       | 2.3    | 2.3                | 2                      | 2                |                  |
| Front left diameter                        | mm 210         | 210       | 120   210    | 210       | 210    | 210                | 180                    | 180              |                  |
| Front right spec 2)                        |                | F         | F            | F         | F      | F                  | F                      | F                |                  |
| Front right rating 3)                      | kW 1.8 - 2.8   | 1.2       | 1.2          | 1.2       | 1.2    | 1.2                | 1.5                    | 1.5              |                  |
| Front right diameter                       | mm 180         | 145       | 145          | 145       | 145    | 145                | 145                    | 145              |                  |
| Rear left spec 2)                          |                |           | F            | F         | F      | F                  | F                      | F                |                  |
| Rear left rating 3)                        | kW 1.4         | 1.4       | 1.2          | 1.2       | 1.2    | 1.2                | 1.5                    | 1.5              |                  |
| Rear left diameter                         | mm 140         | 145       | 145          | 145       | 145    | 145                | 180                    | 145              |                  |
| Rear right spec 2)                         |                | F         | F            | F         | F      | F                  | F                      | F                |                  |
| Rear right rating 3)                       | kW 1.8         | 0.7   1.7 | 1.5   2.4    | 1.7   7   | 1.8    | 1.8                | 2                      | 2                |                  |
| Rear right diameter                        | mm 180         | 120   180 | 170   265    | 180   120 | 180    | 180                | 180                    | 180              |                  |
| Middle front spec                          |                |           |              |           |        |                    |                        |                  | Fast solid plate |
| Middle front rating                        | kW             |           |              |           |        |                    |                        |                  | 1                |
| Middle front diameter                      | mm             |           |              |           |        |                    |                        |                  | 145              |
| Middle rear spec                           |                |           |              |           |        |                    |                        |                  | Fast solid plate |
| Middle rear rating                         | kW             |           |              |           |        |                    |                        |                  | 1.5              |
| Middle rear diameter                       | mm             |           |              |           |        |                    |                        |                  | 180              |
| <b>ELECTRICAL CONNECTION</b>               |                |           |              |           |        |                    |                        |                  |                  |
| Total rating (max.)                        | kW 7.2         | 6.5       | 7            | 6.5       | 6.5    | 6.5                | 7                      | 6                | 2.5              |
| Fuse rating                                | A 30           | 30        | 30           | 30        | 30     | 30                 | 30                     | 30               | 30               |
| <b>SAFETY AND INTERFERENCE SUPPRESSION</b> |                |           |              |           |        |                    |                        |                  |                  |
| Low Voltage Directive (LVD)                | ■              | ■         | ■            | ■         | ■      | ■                  | ■                      | ■                | ■                |
| Electromagnetic Compatibility (EMC)        | ■              | ■         | ■            | ■         | ■      | ■                  | ■                      | ■                | ■                |
| <b>LITERATURE SUPPLIED</b>                 |                |           |              |           |        |                    |                        |                  |                  |
| Operation and installation instructions    | ■              | ■         | ■            | ■         | ■      | ■                  | ■                      | ■                | ■                |
| <b>APPLIANCE DIMENSIONS</b>                |                |           |              |           |        |                    |                        |                  |                  |
| Height (above worktop)                     | mm 3           | 3         | 3            | 3         | 3      | 3   5              |                        | 8                | 4                |
| Width                                      | mm 570         | 576       | 766          | 590       | 570    | 570                | 594                    | 580              | 290              |
| Depth                                      | mm 500         | 506       | 506          | 520       | 500    | 500                | 510                    | 500              | 510              |
| Net weight                                 | kg 11.4        | 11.7      | 10.5         | 7.5       | 7.8    | 7.7                | 11.9                   | 11.9             | 5.9              |
| <b>APERTURE DIMENSIONS 1)</b>              |                |           |              |           |        |                    |                        |                  |                  |
| Height                                     | mm 58          | 58        | 41           | 38        | 41     | 41   38            | 30                     | 30               | 30               |
| Width                                      | mm 560         | 560       | 750          | 560       | 560    | 560                | 560                    | 550              | 270              |
| Depth                                      | mm 490         | 490       | 490          | 490       | 490    | 490                | 480                    | 470              | 490              |
| <b>PACKAGING DIMENSIONS</b>                |                |           |              |           |        |                    |                        |                  |                  |
| Height                                     | mm 115         | 115       | 115          | 115       | 110    | 110                | 120                    | 120              | 120              |
| Width                                      | mm 745         | 745       | 865          | 745       | 665    | 665                | 670                    | 670              | 400              |
| Depth                                      | mm 575         | 575       | 575          | 575       | 570    | 570                | 600                    | 600              | 600              |
| Gross weight                               | kg 12.2        | 12.4      | 11.1         | 8.3       | 8.6    | 8.6                | 12.5                   | 12.5             | 6.2              |

1) Refer to User Instructions before cutting out  
 2) HA=HALOLIGHT zone; D=Dual Circuit zone; O=Oval multi-purpose zone;  
 I=Induction; F=Fast plate/Fast zone  
 \*Hob height: is height above worktop only

# COOKING

| MODEL                                      | CHIMNEY HOODS    |               |              |           |           |              |              |               |               |           |
|--|------------------|---------------|--------------|-----------|-----------|--------------|--------------|---------------|---------------|-----------|
|  | ZHC428AX         | ZHC945AX      | ZHC925AX     | EFC9095DX | EFA9095DX | EFF7071DX    | EFF7070DX    | EFF90001X/W/K | EFF60001X/W/K | EFF70001X |
| <b>SPECIFICATION</b>                       |                  |               |              |           |           |              |              |               |               |           |
| Fan speeds                                 | 5                | 4             | 3            | 4         | 4         | 3            | 3            | 3             | 3             | 3         |
| Control type                               | Push Buttons     | Rotary Switch | Push Buttons | Touch     | Touch     | Push Buttons | Push Buttons | Slider        | Slider        | Slider    |
| Electronic speed control                   | ■                | ■             |              | ■         | ■         |              |              |               |               |           |
| Intensive setting                          | ■                | ■             |              | ■         | ■         |              |              |               |               |           |
| Hob illumination (H=Halogen) Watts         | 4x20 H           | 2x20 H        | 2x20 H       | 2x20 H    | 4x20 H    | 2x40         | 2x20 H       | 2x40          | 2x40          | 2x40      |
| Extraction/recirculation operation         | ■   ■            | ■   ■         | ■   ■        | ■   ■     | ■   ■     | ■   ■        | ■   ■        | ■   ■         | ■   ■         | ■   ■     |
| Saturation indication                      |                  |               |              |           |           |              |              |               |               |           |
| Metal grease filter(s)                     | ■                | ■             | ■            | ■         | ■         | ■            | ■            | ■             | ■             | ■         |
| <b>INSTALLATION HEIGHT FROM:</b>           |                  |               |              |           |           |              |              |               |               |           |
| Electric hob                               | mm 650           | 500           | 500          | 650       | 650       | 650          | 600          | 650           | 650           | 650       |
| Gas hob                                    | mm 650           | 650           | 650          | 650       | 650       | 650          | 650          | 650           | 650           | 650       |
| <b>PERFORMANCE DATA</b>                    |                  |               |              |           |           |              |              |               |               |           |
| Extraction rate free blowing               | max 870          | 600           | 440          | 660       | 660       | 440          | 450          | 450           | 450           | 450       |
| Extraction ca.m3/h                         | max 620          | 490           | 400          | 460       | 460       | 390          | 400          | 400           | 400           | 400       |
| Extraction ca.m3/h intensive               | 820              | 550           |              | 550       | 550       |              |              |               |               |           |
| Recirculation ca.m3/h                      | max 360          | 360           | 280          | 320       | 320       | 290          | 320          | 300           | 300           | 300       |
| Recirculation ca.m3/h intensive            | 440              | 410           |              | 360       | 360       |              |              |               |               |           |
| Noise (max. setting)                       | extraction dB 60 | 63            | 63           | 62        | 62        | 61           | 62           | 61            | 61            | 61        |
| recirculation dB                           | 59               | 67            | 65           | 61        | 67        | 60           | 64           | 60            | 60            | 60        |
| <b>ADDITIONAL EQUIPMENT REQUIRED:</b>      |                  |               |              |           |           |              |              |               |               |           |
| For ducting: Ventilation hose and wall box | ■                | ■             | ■            | ■         | ■         | ■            | ■            | ■             | ■             | ■         |
| Ventilation hose diameter *                | mm 150           | 150           | 150          | 150       | 150       | 150          | 150          | 150           | 150           | 150       |
| For recirculation: Charcoal filter         | Included         | Included      | Included     | EFF72     | EFF72     | EFF72        | TYPE 160     | EFF62         | EFF62         | EFF62     |
| <b>ELECTRICAL CONNECTION</b>               |                  |               |              |           |           |              |              |               |               |           |
| Connected load                             | Watts 410        | 215           | 205          | 245       | 285       | 230          | 210          | 230           | 230           | 230       |
| Fuse rating                                | A 13             | 13            | 13           | 13        | 13        | 13           | 13           | 13            | 13            | 13        |
| <b>SAFETY AND INTERFERENCE SUPPRESSION</b> |                  |               |              |           |           |              |              |               |               |           |
| Low Voltage Directive (LVD)                | ■                | ■             | ■            | ■         | ■         | ■            | ■            | ■             | ■             | ■         |
| Electromagnetic Compatibility (EMC)        | ■                | ■             | ■            | ■         | ■         | ■            | ■            | ■             | ■             | ■         |
| <b>LITERATURE SUPPLIED</b>                 |                  |               |              |           |           |              |              |               |               |           |
| Operation and installation instructions    | ■                | ■             | ■            | ■         | ■         | ■            | ■            | ■             | ■             | ■         |
| <b>APPLIANCE DIMENSIONS 1)</b>             |                  |               |              |           |           |              |              |               |               |           |
| Height for extraction                      | mm 750-1200      | 670-1170      | 670-1105     | 940-1270  | 880-1060  | 678-898      | 750-1165     | 670-925       | 670-925       | 670-925   |
| Height for recirculation (if different)    | mm               |               |              | 815-1270  | 880-1120  |              |              |               |               |           |
| Width                                      | mm 448           | 898           | 898          | 898       | 898       | 598-698      | 700          | 898           | 598           | 698       |
| Depth                                      | mm 483           | 500           | 500          | 490       | 650       | 520          | 505          | 502           | 502           | 502       |
| Net weight                                 | kg 29            | 23.6          | 23.5         | 17.6      | 33.5      | 19.4         | 15.7         | 12.6          | 11.2          | 11.2      |
| <b>PACKAGING DIMENSIONS</b>                |                  |               |              |           |           |              |              |               |               |           |
| Height                                     | mm 915           | 540           | 1090         | 975       | 990       | 775          | 585          | 645           | 645           | 645       |
| Width                                      | mm 995           | 1090          | 540          | 405       | 760       | 405          | 815          | 980           | 680           | 680       |
| Depth                                      | mm 616           | 617           | 617          | 645       | 525       | 645          | 440          | 410           | 410           | 410       |
| Gross weight                               | kg 40.7          | 32.3          | 31.1         | 23.6      | 43        | 23.7         | 19.5         | 17.2          | 14.2          | 14.2      |

1) For installation aperture dimensions see installation instructions  
 # 120cm outlet adaptor included  
 \*CDK5F  
 120mm (5") diameter flexible ducting kit. 1 metre length. For use with all hoods up to 1 metre ducting.  
 CDK5FR  
 120mm (5") diameter ducting kits for ducting of hoods situated away from exterior wall, up to 3 metres.  
 CDK6FR  
 150mm (6") diameter ducting kits for ducting of hoods situated away from exterior wall, up to 3 metres.

## COOKING

|  | HOODS | CANOPY      | TELESCOPIC | INTEGRATED | TRADITIONAL   |
|--|-------|-------------|------------|------------|---------------|
| MODEL                                      |       |             |            |            |               |
|  |       | EFF652002IS | EFF60032X  | EFF6001IS  | EFF60004K/WIX |
| <b>SPECIFICATION</b>                       |       |             |            |            |               |
| Fan speeds                                 |       | 3           | 3          | 3          | 3             |
| Control type                               |       | Slider      | Slider     | Slider     | Slider        |
| Electronic speed control                   |       |             |            |            |               |
| Intensive setting                          |       |             |            |            |               |
| Hob illumination (H=Halogen) Watts         |       | 2x40        | 2x40       | 2x40       | 1x40          |
| Extraction/recirculation operation         |       | ■   ■       | ■   ■      | ■   ■      | ■   ■         |
| Saturation indication                      |       | on filter   |            | on filter  | on filter     |
| Metal grease filter                        |       |             | ■          |            |               |
| <b>INSTALLATION HEIGHT FROM:</b>           |       |             |            |            |               |
| Electric hob                               | mm    | 650         | 500        | 500        | 650           |
| Gas hob                                    | mm    | 650         | 650        | 700        | 650           |
| <b>PERFORMANCE DATA</b>                    |       |             |            |            |               |
| Extraction rate free blowing               | max   | 280         | 310        | 220        | 180           |
| Extraction ca.m3/h                         | max   | 250         | 280        | 210        | 170           |
| Extraction ca.m3/h intensive               |       |             |            |            |               |
| Recirculation ca.m3/h                      | max   | 210         | 230        | 110        | 150           |
| Recirculation ca.m3/h intensive            |       |             |            |            |               |
| Noise (max. setting) extraction            | dB    | 61          | 63         | 58         | 59            |
| recirculation                              | dB    | 60          | 62         | 62         | 58            |
| <b>ADDITIONAL EQUIPMENT REQUIRED:</b>      |       |             |            |            |               |
| For ducting: Ventilation hose and wall box |       | ■           | ■          | ■          | ■             |
| Ventilation hose diameter *                | mm    | 120         | 120        | 100        | 120           |
| For recirculation: Charcoal filter         |       | EFF70       | EFF70      | TYPE 29    | EFF57         |
| <b>ELECTRICAL CONNECTION</b>               |       |             |            |            |               |
| Connected load                             | Watts | 195         | 215        | 230        | 135           |
| Fuse rating                                | A     | 13          | 13         | 13         | 13            |
| <b>SAFETY AND INTERFERENCE SUPPRESSION</b> |       |             |            |            |               |
| Low Voltage Directive (LVD)                |       | ■           | ■          | ■          | ■             |
| Electromagnetic Compatibility (EMC)        |       | ■           | ■          | ■          | ■             |
| <b>LITERATURE SUPPLIED</b>                 |       |             |            |            |               |
| Operation and installation instructions    |       | ■           | ■          | ■          | ■             |
| <b>APPLIANCE DIMENSIONS 1)</b>             |       |             |            |            |               |
| Height for extraction                      | mm    | 204         | 175        | 400        | 150           |
| Height for recirculation (if different)    | mm    |             |            |            |               |
| Width                                      | mm    | 522         | 598        | 598        | 598           |
| Depth                                      | mm    | 284         | 280        | 270        | 482           |
| Net weight                                 | kg    | 4.8         | 7.6        | 9.3        | 7.2           |
| <b>PACKAGING DIMENSIONS</b>                |       |             |            |            |               |
| Height                                     | mm    | 290         | 255        | 550        | 645           |
| Width                                      | mm    | 605         | 660        | 720        | 205           |
| Depth                                      | mm    | 370         | 360        | 395        | 545           |
| Gross weight                               | kg    | 5.8         | 8.7        | 10.5       | 8.2           |

1) For installation aperture dimensions see installation instructions

# 120mm outlet adaptor included

\*CDK5FR - 120mm (5") diameter flexible ducting kit, 1 metre length. For use with all hoods up to 1 metre ducting.  
 \*CDK5FR - 120mm (5") diameter ducting kits for ducting of hoods situated away from exterior wall, up to 3 metres.  
 \*CDK6FR - 150mm (6") diameter ducting kits for ducting of hoods situated away from exterior wall, up to 3 metres.

## COOLING

| MODEL  | ZJB9476X   | ZBB7266                             | ZBB6286                   | ZBB7294        | ZBB6284              | ZBB6244        |
|--|--|-------------------------------------|---------------------------|----------------|----------------------|----------------|
|  | 4 Door Frost free Fridge freezer Stainless Steel | Total No-frost 50:50 Fridge freezer | Frost free Fridge freezer | Fridge freezer | 50:50 Fridge freezer | Fridge freezer |
| <b>FRIDGE FEATURES</b>                                 |  |                                     |                           |                |                      |                |
| Defrost  | auto   | auto                                | auto                      | auto           | auto                 | auto           |
| Electronic controls with LCD display                   |  | ■                                   |                           |                |                      |                |
| SET Electronic controls                                | ■  |                                     | ■                         |                |                      |                |
| Electromechanical temperature controls                 |  |                                     | ■                         | ■              | ■                    | ■              |
| Adjustable thermostat                                  | coin/knob  |                                     | Knob                      | Knob           | Knob                 | Knob           |
| Dairy compartment                                      | 2  | ■                                   | ■                         | ■              | ■                    | ■              |
| Full width can shelves                                 | 2  | 2                                   | 2                         | 2              | 2                    | 2              |
| 1/2 width sliding shelf                                |  |                                     | ■                         | ■              |                      |                |
| Bottle rack with grippers                              | 2  | ■                                   | ■                         | ■              | ■                    | ■              |
| MINI DAC/Supercooling                                  | ■  | ■                                   |                           |                |                      |                |
| Glass shelves (full depth)                             | 3  | 2                                   | 2                         | 2              | 2                    | 2              |
| Glass shelves (half depth)                             | 2  | 2                                   | 2                         | 2              | 2                    | 2              |
| Flexible shelf positions                               | ■  | ■                                   | ■                         | ■              | ■                    | ■              |
| Large telescopic drawer with divider for salad veg etc | ■  |                                     |                           |                |                      |                |
| 2 half width salad bins with full width glass cover    |  | ■                                   | ■                         | ■              | ■                    | ■              |
| Interior light   | 2  | ■                                   | ■                         | ■              | ■                    | ■              |
| Egg container  | 2  | ■                                   | ■                         | ■              | ■                    | ■              |
| <b>FREEZER FEATURES</b>                                |  |                                     |                           |                |                      |                |
| Frost Free   | ■  | ■                                   | ■                         |                |                      |                |
| Defrost - freezer                                      | auto   | auto                                | auto                      | manual         | manual               | manual         |
| Electronic temperature controls                        | ■  | ■                                   | ■                         |                |                      |                |
| Electronic controls with LCD display                   |  | ■                                   |                           |                |                      |                |
| On LED (Green)   | ■  | In LCD Display                      | ■                         |                |                      |                |
| Fast freeze function with timed auto switch off        | ■  | In LCD Display                      | ■                         |                |                      |                |
| Fast freeze LED (Yellow)                               | ■  | In LCD Display                      | ■                         |                |                      |                |
| High temperature warning LED (Red)                     | ■  | In LCD Display                      | ■                         |                |                      |                |
| High temperature warning audible buzzer                | ■  | ■                                   | ■                         |                |                      |                |
| Freezer compartments (drawers)                         | 4  | 4                                   | 3                         | 3              | 4                    | 2              |
| Transparent freezer drawers                            | ■  | ■                                   | ■                         | ■              | ■                    | ■              |
| Freezer calendar                                       | ■  | ■                                   | ■                         | ■              | ■                    | ■              |
| Ice tray   | ■  | ■                                   | ■                         | ■              | ■                    | ■              |
| <b>OTHER FEATURES</b>                                  |  |                                     |                           |                |                      |                |
| Adjustable feet  | ■  |                                     |                           |                |                      |                |
| Reversible doors                                       |  | ■                                   | ■                         | ■              | ■                    | ■              |
| 100% CFC Free  | ■  | ■                                   | ■                         | ■              | ■                    | ■              |
| 100% HFC Free  | ■  | ■                                   | ■                         | ■              | ■                    | ■              |
| Fridge freezer split                                   |  | 50:50                               | 70:30                     | 70:30          | 50:50                | 60:40          |
| <b>ENERGY EFFICIENCY INFORMATION</b>                   |  |                                     |                           |                |                      |                |
| Energy efficiency class*                               | A  | A                                   | A                         | A              | A                    | A              |
| Energy consumption kW/year**                           | 416  | 335                                 | 314                       | 318            | 321                  | 292            |
| Noise IEC 704-3 dB(A)                                  | 40   | 38                                  | 38                        | 36             | 36                   | 36             |
| Gross capacity fridge litres (cu.ft)                   | 342 (12.1)                                       | 164 (5.8)                           | 214 (7.6)                 | 214 (7.6)      | 173 (6.1)            | 173 (6.1)      |
| Net capacity fridge litres (cu.ft)                     | 338 (11.9)                                       | 162 (5.7)                           | 210 (7.4)                 | 210 (7.4)      | 170 (6.0)            | 170 (6.0)      |
| Gross capacity freezer litres (cu.ft)                  | 128 (4.5)  | 91 (3.2)                            | 68 (2.4)                  | 76 (2.7)       | 110 (3.9)            | 62 (2.2)       |
| Net capacity freezer litres (cu.ft)                    | 96 (3.4)   | 78 (2.7)                            | 55 (1.9)                  | 70 (2.5)       | 92 (3.3)             | 60 (2.1)       |
| Frozen food rating                                     | 4 star   | 4 star                              | 4 star                    | 4 star         | 4 star               | 4 star         |
| Power cut safe hours***                                | 14   | 25                                  | 13                        | 20             | 18                   | 20             |
| Freezing capacity Kg/24 hours                          | 13   | 10                                  | 4                         | 4              | 10                   | 6              |
| Climate class****                                      | SN/T   | SN/T                                | SN/ST                     | SN/ST          | SN/ST                | SN             |
| <b>ELECTRICAL CONNECTION</b>                           |  |                                     |                           |                |                      |                |
| Connected load   | Watts  | 240                                 | 160                       | 160            | 120                  | 100            |
| Fuse rating  | A  | 13                                  | 13                        | 13             | 13                   | 13             |
| <b>PRODUCT DIMENSIONS</b>                              |  |                                     |                           |                |                      |                |
| Height   | mm   | 1900-1950                           | 1772                      | 1772           | 1772                 | 1441           |
| Width  | mm   | 856                                 | 540                       | 540            | 540                  | 540            |
| Depth  | mm   | 542                                 | 547                       | 547            | 547                  | 547            |
| Net weight   | kg   | 104.0                               | 59.5                      | 57.5           | 57.0                 | 48.0           |
| <b>BUILT-IN DIMENSIONS</b>                             |  |                                     |                           |                |                      |                |
| Built-in height  | mm   | 1900-1950                           | 1780                      | 1780           | 1780                 | 1446           |
| Built-in width   | mm   | 860                                 | 560                       | 560            | 560                  | 560            |
| Built-in depth   | mm   | 550                                 | 550                       | 550            | 550                  | 550            |
| Door fixing  |  | Door on door                        | Slider                    | Slider         | Slider               | Slider         |
| <b>PACKAGING INFORMATION</b>                           |  |                                     |                           |                |                      |                |
| Height   | mm   | 2020                                | 1850                      | 1860           | 1860                 | 1530           |
| Width  | mm   | 920                                 | 600                       | 610            | 610                  | 610            |
| Depth  | mm   | 600                                 | 600                       | 620            | 620                  | 620            |
| Gross weight   | kg   | 125.0                               | 64.0                      | 62.0           | 62.0                 | 52.0           |



# COOLING

| MODEL  | ZBA6160                 | ZBA6230                 | ZQS6140                     | ZQS6124                                  | ZBF6114           | ZQF6114               |
|--|-------------------------|-------------------------|-----------------------------|--|-------------------|-----------------------|
|  | In-column larder fridge | In-column larder fridge | Under counter larder fridge | Under counter fridge with 4 star freezer | In-column freezer | Under counter freezer |
| <b>FRIDGE FEATURES</b>   |                         |                         |                             |  |                   |                       |
| Defrost  | auto                    | auto                    | auto                        | auto                                     |                   |                       |
| Electromechanical temperature controls                               | ■                       | ■                       | ■                           | ■  |                   |                       |
| Adjustable thermostat coin/knob                                      | Knob                    | Knob                    | Knob                        | Knob                                     |                   |                       |
| Dairy compartment  | ■                       | ■                       | ■                           | ■  |                   |                       |
| Full width can shelves   | 2                       | 2                       |                             |  |                   |                       |
| 1/2 width sliding shelf  |                         |                         | ■                           | ■  |                   |                       |
| Bottle rack with grippers  | ■                       | ■                       | ■                           | ■  |                   |                       |
| Glass shelves (full depth)   | 2                       | 4                       | 2                           | 1  |                   |                       |
| Glass shelves (half depth)   | 2                       |                         | 2                           | 2  |                   |                       |
| Flexible shelf positions   | ■                       | ■                       | ■                           | ■  |                   |                       |
| Full width transparent salad bin with 2 half width hinged glass lids |                         |                         | ■                           | ■  |                   |                       |
| Full width salad bin with glass lid                                  | ■                       |                         |                             |  |                   |                       |
| 2 half width salad bins with full width glass cover                  |                         | ■                       |                             |  |                   |                       |
| Interior light   | ■                       | ■                       | ■                           | ■  |                   |                       |
| Egg container  | ■                       | ■                       | ■                           | ■  |                   |                       |
| <b>FREEZER FEATURES</b>  |                         |                         |                             |  |                   |                       |
| Defrost - freezer  |                         |                         |                             | manual                                   | manual            | manual                |
| Electronic temperature controls                                      |                         |                         |                             |  | ■                 | ■                     |
| Adjustable thermostat coin/knob                                      |                         |                         |                             | Knob                                     | Knob              |                       |
| On LED (Green)   |                         |                         |                             | ■  | ■                 | ■                     |
| Fast freeze function with timed auto switch off                      |                         |                         |                             | ■  | ■                 | ■                     |
| Fast freeze LED (Yellow)   |                         |                         |                             | ■  | ■                 | ■                     |
| High temperature warning LED (Red)                                   |                         |                         |                             | ■  | ■                 | ■                     |
| High temperature warning audible buzzer                              |                         |                         |                             |  | ■                 | ■                     |
| Door open warning audible buzzer                                     |                         |                         |                             |  | ■                 | ■                     |
| Freezer compartments (flap/drawers)                                  |                         |                         |                             | 1/0                                      | 0/4               | 0/4                   |
| Transparent freezer compartments                                     |                         |                         |                             |  | ■                 | ■                     |
| Freezer calendar   |                         |                         |                             |  | ■                 | ■                     |
| Ice tray   |                         |                         |                             |  | ■                 | ■                     |
| Ice scraper  |                         |                         |                             | ■  | ■                 | ■                     |
| <b>OTHER FEATURES</b>  |                         |                         |                             |  |                   |                       |
| Adjustable feet  |                         |                         | ■                           | ■  |                   | ■                     |
| Reversible doors   | ■                       | ■                       | ■                           | ■  | ■                 | ■                     |
| 100% CFC Free  | ■                       | ■                       | ■                           | ■  | ■                 | ■                     |
| 100% HFC Free  | ■                       | ■                       | ■                           | ■  | ■                 | ■                     |
| Matching fridge/freezer  | ZBF6114                 |                         | ZQF6114                     | ZQF6114                                  | ZBA6160           | ZQS6140               |
| <b>ENERGY EFFICIENCY INFORMATION</b>                                 |                         |                         |                             |  |                   |                       |
| Energy efficiency class*   | A                       | A                       | A                           | A  | A                 | A                     |
| Energy consumption kWh/year**  | 150                     | 161                     | 146                         | 212                                      | 208               | 208                   |
| Noise IEC 704-3 dB(A)  | 38                      | 36                      | 35                          | 37                                       | 36                | 38                    |
| Gross capacity fridge litres (cu.ft)                                 | 158 (5.6)               | 230 (8.1)               | 142 (5.0)                   | 105 (3.7)                                |                   |                       |
| Net capacity fridge litres (cu.ft)                                   | 154 (5.5)               | 228 (8.1)               | 138 (4.8)                   | 103 (3.6)                                |                   |                       |
| Gross capacity freezer litres (cu.ft)                                |                         |                         |                             | 17 (0.6)                                 | 110 (3.9)         | 108 (3.8)             |
| Net capacity freezer litres (cu.ft)                                  |                         |                         |                             | 17 (0.6)                                 | 94 (3.3)          | 98 (3.4)              |
| Frozen food rating   |                         |                         |                             | 4 star                                   | 4 star            | 4 star                |
| Power cut safe hours***  |                         |                         |                             | 13                                       | 20                | 20                    |
| Freezing capacity Kg/24 hours  |                         |                         |                             | 2.5                                      | 16                | 18                    |
| Climate class****  | SN/ST                   | SN/ST                   | SN/ST                       | SN/ST                                    | SN/ST             | SN/ST                 |
| <b>ELECTRICAL CONNECTION</b>   |                         |                         |                             |  |                   |                       |
| Connected load Watts   | 100                     | 140                     | 90                          | 90                                       | 110               | 120                   |
| Fuse rating A  | 13                      | 13                      | 13                          | 13                                       | 13                | 13                    |
| <b>PRODUCT DIMENSIONS</b>  |                         |                         |                             |  |                   |                       |
| Height mm  | 873                     | 1218                    | 815/885                     | 815/885                                  | 873               | 815/885               |
| Width mm   | 540                     | 540                     | 596                         | 596                                      | 540               | 596                   |
| Depth mm   | 549                     | 549                     | 550                         | 550                                      | 549               | 550                   |
| Net weight kg  | 30                      | 43                      | 34                          | 37                                       | 33.5              | 38                    |
| <b>BUILT-IN DIMENSIONS</b>   |                         |                         |                             |  |                   |                       |
| Built-in height mm   | 880                     | 1225                    | 820/890                     | 820/890                                  | 880               | 820/890               |
| Built-in width mm  | 560                     | 560                     | 600                         | 600                                      | 560               | 600                   |
| Built-in depth mm  | 550                     | 550                     | 550                         | 550                                      | 550               | 550                   |
| Door fixing  | Slider                  | Slider                  | Door on door                | Door on door                             | Slider            | Door on door          |
| <b>PACKAGING INFORMATION</b>   |                         |                         |                             |  |                   |                       |
| Height mm  | 960                     | 1300                    | 880                         | 880                                      | 960               | 880                   |
| Width mm   | 610                     | 600                     | 670                         | 670                                      | 600               | 670                   |
| Depth mm   | 610                     | 620                     | 600                         | 600                                      | 620               | 600                   |
| Gross weight kg  | 33.0                    | 46.0                    | 37.0                        | 40.0                                     | 36.0              | 41.0                  |

Matt silver inclinable bottle rack for wine and large soft drink bottles - optional extra. Order BTLRACKS, suitable for all Zanussi fridge freezers  
 \* Energy efficiency class based on a scale of A+ (most efficient) to G (least efficient)  
 \*\* Based on standard test results for 24 hours in accordance with EN153. Actual consumption will depend on how the appliance is used and where it is located  
 \*\*\* Time for food temperature to rise from -18°C to -9°C with the power off and the door remaining closed  
 \*\*\*\* Climate class - the product is suitable for use in ambient temperatures of SN: 10-32°C, N:16-32°C, ST: 18-38°C, T: 18-43°C

# DISHWASHING

| MODEL  | ZD16000X              | ZD11420          | ZD1312           | ZD1201           | ZD1140           | ZD13101                   | ZD1122           |
|--|-----------------------|------------------|------------------|------------------|------------------|---------------------------|------------------|
| Capacity (number of IEC place settings)      | 12                    | 12               | 12               | 12               | 12               | 9                         | 12               |
| <b>CONTROLS</b>                              |                       |                  |                  |                  |                  |                           |                  |
| Design                                       | Square                | Fully Integrated | Fully Integrated | Fully Integrated | Fully Integrated | Slimline Fully Integrated | Fully Integrated |
| Fuzzy Logic                                  | ■                     | ■                |                  |                  |                  |                           |                  |
| Electronic controls                          | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| LED programme progress indicator             |                       |                  | ■                | ■                | ■                | ■                         | ■                |
| Time to programme end display                | ■                     | ■                |                  |                  |                  |                           |                  |
| End of programme indicator                   | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| End of programme alarm                       |                       | ■                | ■                | ■                | ■                | ■                         |                  |
| Delay start                                  | ■                     | ■                | ■                | ■                |                  |                           |                  |
| Salt refill indicator                        | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Rinse aid refill indicator                   | ■                     | ■                | ■                |                  |                  |                           |                  |
| Half load option                             |                       | ■                |                  |                  |                  |                           |                  |
| Number of programmes                         | 8                     | 7                | 5                | 5                | 4                | 5                         | 5                |
| Number of temperature options                | 5                     | 4                | 4                | 2                | 2                | 2                         | 3                |
| <b>INTERIOR</b>                              |                       |                  |                  |                  |                  |                           |                  |
| Upper basket height                          | Quick Lift            | Quick Lift       | Adjustable       | Adjustable       | Adjustable       | Adjustable                | Adjustable       |
| Cup shelves                                  | 4 foldable            | 4 foldable       | 4 foldable       | 4 foldable       | 4 foldable       | 3 (2 foldable)            | 2 foldable       |
| Lower basket plate racks                     | 4 foldable            | 4 foldable       | Fixed            | Fixed            | Fixed            | Fixed                     | Fixed            |
| Basket handles                               | Delta Silver          | Delta Silver     | Delta Grey       | Wire             | Wire             | Wire                      | Wire             |
| Cutlery basket                               | Divdable Delta Silver | Delta Silver     | Delta Grey       | Delta Grey       | Delta Grey       | Delta Grey                | Delta Grey       |
| Automatic rinse aid dispenser                | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Automatic detergent dispenser                | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Anti flood device                            | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Drying with hidden heater                    | Active                | Active           | Active           | Active           | Residual         | Residual                  | Residual         |
| Stainless steel interior                     | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| <b>INSTALLATION FEATURES</b>                 |                       |                  |                  |                  |                  |                           |                  |
| Cold water fill                              | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Water pressure min/max (psi)                 | 7/110                 | 7/110            | 7/110            | 7/110            | 7/110            | 7/110                     | 7/110            |
| Equipose door                                | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Double fulcrum hinge                         | ■                     | ■                |                  |                  |                  |                           |                  |
| Drawer-line adjustment                       |                       |                  |                  |                  |                  |                           | 30mm             |
| Worktop steam protection                     | Metal Bar             | Metal Bar        | Aluminium Foil   | Aluminium Foil   | Aluminium Foil   | Aluminium Foil            | Aluminium Foil   |
| Top & side fixing brackets                   | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Recessed plinth                              | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| Feet - 3 (front adjustment block)            | ■                     | ■                | ■                | ■                | ■                | ■                         | ■                |
| <b>ENERGY EFFICIENCY INFORMATION</b>         |                       |                  |                  |                  |                  |                           |                  |
| Energy efficiency class**                    | A                     | A                | A                | A                | A                | A                         | A                |
| Energy consumption kWh                       | 1.05                  | 1.05             | 1.05             | 1.05             | 1.05             | 0.8                       | 1.05             |
| Wash performance***                          | A                     | A                | A                | A                | A                | A                         | A                |
| Drying performance***                        | A                     | A                | B                | A                | B                | B                         | B                |
| Noise dB(A) to IEC 704-3                     | 47dB(a)               | 48dB(a)          | 51dB(a)          | 51dB(a)          | 53dB(a)          | 54dB(a)                   | 53dB(a)          |
| Programme time**** mins                      | 160                   | 160              | 160              | 140              | 140              | 130                       | 140              |
| Water consumption litres/cycle               | 14                    | 14               | 14               | 16               | 16               | 14                        | 16               |
| Average annual energy consumption kWh/year   | 231                   | 231              | 231              | 231              | 231              | 176                       | 231              |
| Average annual water consumption litres/year | 3080                  | 3080             | 3080             | 3520             | 3520             | 3080                      | 3520             |
| <b>ELECTRICAL CONNECTION</b>                 |                       |                  |                  |                  |                  |                           |                  |
| Connected load kW                            | 2.2                   | 2.2              | 2.2              | 2.2              | 2.2              | 2.2                       | 2.2              |
| Fuse rating A                                | 13                    | 13               | 13               | 13               | 13               | 13                        | 13               |
| <b>PRODUCT DIMENSIONS</b>                    |                       |                  |                  |                  |                  |                           |                  |
| Height mm                                    | 818                   | 818              | 818              | 818              | 818              | 818                       | 818              |
| Width mm                                     | 596                   | 596              | 596              | 596              | 596              | 446                       | 596              |
| Depth mm                                     | 575                   | 555              | 555              | 555              | 555              | 555                       | 575              |
| Net weight kg                                | 45.7                  | 36.9             | 36.9             | 37.1             | 36.9             | 33                        | 38               |
| <b>FURNITURE DOOR DIMENSIONS</b>             |                       |                  |                  |                  |                  |                           |                  |
| Height mm                                    | 120                   | 660-720          | 660-720          | 660-720          | 660-720          | 660-720                   | 540-604          |
| Width mm                                     | 596                   | 596              | 596              | 596              | 596              | 445                       | 596              |
| Weight kg                                    | N/A****               | 2-10             | 2-10             | 2-10             | 2-10             | 1.5-6                     | 2-8              |
| <b>PACKAGING DIMENSIONS</b>                  |                       |                  |                  |                  |                  |                           |                  |
| Height mm                                    | 910                   | 902              | 902              | 902              | 902              | 910                       | 902              |
| Width mm                                     | 650                   | 635              | 635              | 635              | 635              | 500                       | 635              |
| Depth mm                                     | 680                   | 680              | 680              | 680              | 680              | 680                       | 680              |
| Gross weight kg                              | 49.0                  | 38.6             | 38.9             | 38.6             | 38.6             | 34.8                      | 39.8             |

\* Energy consumption is stated in kWh per standard test cycle, using cold water fill. Actual consumption will depend on how the appliance is used.  
 \*\* Estimated annual consumption based on 220 washing cycles.  
 \*\*\* Models with an 'A' rated classification offer a higher performance than those with a 'G' rating.  
 \*\*\*\* Time taken for a standard test cycle, using cold water fill.  
 \*\*\*\*\* These models need a false drawer panel to be fitted below the stainless steel door (similar to the infill panel located below the under counter single oven).

## LAUNDRY

| MODEL   | LAUNDRY         |                 |              |
|---|-----------------|-----------------|--------------|
|   | ZW12125         | ZW11125         | ZK1245       |
|   | Washing Machine | Washing Machine | Washer Dryer |
| Wash system   | Jetsystem       | Aquacycle       | Jetsystem    |
| Wash capacity   | 6               | 6               | 6            |
| Dry capacity  |                 |                 | 3            |
| Spin speed  | 1200            | 1200            | 1400         |
| <b>CONTROLS</b>   |                 |                 |              |
| LED display   | ■               |                 | ■            |
| Electronic controls   | ■               | ■               | ■            |
| Rotary controls   | 1               | 1               | 1            |
| Push buttons  | 9               | 4               | 9            |
| Programme progress LEDs   | ■               |                 | ■            |
| Delay timer   | ■               |                 | ■            |
| Display for programme time, delay time and countdown to programme end | ■               |                 | ■            |
| <b>PROGRAMMES</b>   |                 |                 |              |
| Cottons/linens  | ■               | ■               | ■            |
| Cotton economy  | ■               |                 | ■            |
| Synthetics  | ■               | ■               | ■            |
| Easy iron   | ■               |                 | ■            |
| Delicates   | ■               | ■               | ■            |
| Wool  | ■               | ■               |              |
| Handwash  |                 |                 | ■            |
| Mini 30 minutes   | ■               |                 | ■            |
| Worn once 30°   |                 | ■               |              |
| Additional programmes   | ■               |                 | ■            |
| 2 temperature drying  |                 |                 | ■            |
| <b>OPTIONS</b>  |                 |                 |              |
| Quick wash  | ■               | ■               | ■            |
| Temperature selection/cold wash                                       | ■               | ■               | ■            |
| Spin speed reduction/rinse hold                                       | ■               |                 | ■            |
| Prewash   | ■               |                 | ■            |
| Extra rinse   | ■               | ■               | ■            |
| Daily wash  | ■               |                 | ■            |
| Easy ironing  | ■               |                 |              |
| Drying time   |                 |                 | ■            |
| <b>FEATURES</b>   |                 |                 |              |
| Large porthole  | ■               | ■               | ■            |
| Wide door opening   | ■               | ■               | ■            |
| <b>INFORMATION</b>  |                 |                 |              |
| Wash/spin only  |                 |                 |              |
| Energy class (wash/spin only) <sup>1</sup>                            | A+              | A+              | A+           |
| Energy consumption <sup>2</sup>                                       | 0.85            | 1.15            | 0.85         |
| Average annual energy consumption <sup>4</sup>                        | 170             | 230             | 170          |
| Water consumption <sup>2</sup>  | 42              | 46              | 46           |
| Average annual water consumption <sup>4</sup>                         | 9800            | 11800           | 9800         |
| Washing programme time <sup>2</sup>                                   | 145             | 140             | 145          |
| Washing performance (A-G) <sup>2</sup>                                | A               | A               | A            |
| Spin efficiency (A-G) <sup>2</sup>                                    | B               | B               | B            |
| Water extraction efficiency   | 53              | 60              | 53           |
| Wash/spin/dry - always using the dryer                                |                 |                 |              |
| Energy class (wash/spin/dry) <sup>1</sup>                             |                 |                 | B            |
| Energy consumption <sup>3</sup>                                       |                 |                 | 4.45         |
| Average annual energy consumption <sup>5</sup>                        |                 |                 | 890          |
| Water consumption <sup>3</sup>  |                 |                 | 120          |
| Average annual water consumption <sup>5</sup>                         |                 |                 | 24000        |
| Washing programme time <sup>3</sup>                                   |                 |                 | 235          |
| Washing performance   |                 |                 | A            |
| Water extraction efficiency   |                 |                 | 53           |
| <b>ELECTRICAL AND WATER CONNECTION</b>                                |                 |                 |              |
| Voltage/frequency   | 240/50          | 240/50          | 240/50       |
| Connected load  | 2050            | 2050            | 2050         |
| Fuse rating   | A               | 13              | 13           |
| Water fill  | Cold            | Cold            | Cold         |
| <b>APPLIANCE DIMENSIONS</b>   |                 |                 |              |
| Height  | 820             | 820             | 820          |
| Width   | 600             | 600             | 600          |
| Depth   | 541             | 541             | 541          |
| Net Weight  | 73.3            | 67.3            | 78.3         |
| <b>BUILT-IN DIMENSIONS*</b>   |                 |                 |              |
| Built-in height   | 820             | 820             | 820          |
| Built-in width  | 600             | 600             | 600          |
| Built-in depth  | 600             | 600             | 600          |
| <b>PACKAGED DIMENSIONS</b>  |                 |                 |              |
| Height  | 900             | 900             | 900          |
| Width   | 640             | 640             | 640          |
| Depth   | 650             | 650             | 650          |
| Gross weight  | 75.5            | 69.5            | 80.5         |

\* PD10 kit for 50mm extra height - optional extra  
 1) Models with an 'A' rated classification offer a higher performance than those with a 'G' rating  
 2) Based on standard test results for 60°C cotton cycle  
 3) Based on standard test results for 60°C cotton cycle and "dry cotton" drying cycle  
 4) Average annual consumption for a 4 person household based on 200 standard 60°C cotton cycles, never using the dryer  
 5) Average annual consumption for a 4 person household based on 200 standard 60°C cotton cycles, always using the dryer

# INSTALLATION DIAGRAMS



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>