

RANGE COMPOSITION

The range of water softeners has been specifically designed for the range of ovens and single tank dishwashers in order to provide an economical form of water treatment that will reduce the build up of scale on the crockery and inside the machine itself.

The range consists of 4 models, 3 models for dishwashers including automatic and manual versions for ovens.



ADM2-ADM-ADAU

WATER SOFTENERS **ZANUSSI** PROFESSIONAL

FUNCTIONAL AND CONSTRUCTION FEATURES

WATER SOFTENER ADM2

- ◆ The water softener ADM2 has been designed specifically for medium sized dishwashers such as LS9, LS10 e LS14.
- ◆ Operating pressure between 1 and 8 bar.
- ◆ Incorporates 20 litre cylinder in stainless steel AISI 304 with 15 litres of resin
- ◆ Every regeneration cycle requires 2,5 kg salt consumption.
- ◆ Water connection between 5°C to 15°C.
- ◆ Maximum flow rate 1000 l/h.
- ◆ Quantity of soft water depending on hardness according to French regulation:
 - 20°- 1900 lt
 - 30°- 1500 lt
 - 40°- 1350 lt
 - 60°- 1050 lt
 - 80°- 750 lt
- ◆ Quantity of soft water depending on hardness according to German regulation:
 - 11°- 1900 lt
 - 17°- 1500 lt
 - 22°- 1350 lt
 - 33°- 1050 lt
 - 44°- 750 lt
- ◆ All models comply with the standards required by the main international approval bodies and are **CE** marked.

WATER SOFTENER ADM

- ◆ ADM has been designed specifically for smaller dishwashers such as LS5, LS6 and LU7.
- ◆ Operating pressure between 1 and 8 bar.
- ◆ Incorporates 12 litre cylinder in stainless steel 304 AISI with 9 litres of resin.
- ◆ Every regeneration cycle requires 1,5 kg of salt.
- ◆ Water connection between 5°C to 15°C.
- ◆ Maximum flow rate 1000l/h.
- ◆ Quantity of soft water depending on hardness according to French regulation:
 - 20°- 1900 lt
 - 30°- 1500 lt
 - 40°- 1350 lt
 - 60°- 1050 lt
 - 80°- 750 lt
- ◆ Quantity of soft water depending on hardness according to German regulation:
 - 11°- 1900 lt
 - 17°- 1500 lt
 - 22°- 1350 lt
 - 33°- 1050 lt
 - 44°- 750 lt

WATER SOFTENER ADAU

- ◆ ADAU has been designed specifically for smaller dishwashers such as LS5 and LS6 and LU7 and consists of 2x24 volt solenoid valves that are linked to an electronic control board that set the regenerating cycles.
- ◆ Automatic regeneration allows programming of 3 regeneration cycles per week: 1 every week, 2 every 4 days, 3 every 2 days.
- ◆ Operating pressure between 2 and 8 bar.
- ◆ Includes back up battery to store input data during power cuts
- ◆ Semi automatic regeneration is via push button.
- ◆ Incorporates 8 litre cylinder in stainless steel 304 AISI with 5,6 litres of resin.
- ◆ Min/maximum flow rate 400/900 l/h.
- ◆ Every regeneration cycle requires 1 kg of salt.
- ◆ Water connection between 5°C and 15°C.

| TECHNICAL DATA | | | |
|--------------------------|----------------|---------------|----------------|
| CHARACTERISTICS | MODELS | | |
| | ADM2 860430 | ADM 860412 | ADAU 860413 |
| External dimensions - mm | | | |
| width | 190 | 190 | 245 |
| depth | 190 | 190 | 480 |
| height | 900 | 515 | 560 |
| Net weight - kg. | 19 | 19 | 19 |

WATER SOFTENERS

ADM2-ADM-ADAU

◆ Quantity of soft water depending on hardness according to French regulation:

20° - 1200 lt
30° - 1000 lt
40° - 900 lt
60° - 700 lt
80° - 500 lt

◆ Quantity of soft water depending on hardness according to German regulation:

11° - 1200 lt
17° - 1000 lt
22° - 900 lt
33° - 700 lt
44° - 500 lt



www.zanussiprofessional.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>