

300-HW SERIES

HOT FOOD DROP-IN WELL





- The gentle heating capability of HALO HEAT significantly extends hot food holding life without continuing the cooking process.
- Provides a more appealing product with better appearance and fresher taste.
- Front-of-the-house use with an existing counter, overhead lighting, and sneeze guard system or drop into a prep table for hot food plating convenience.
- Easy drop-in installation without the need of water or drainage connections and the related installation and water usage costs.
- Maintenance savings with the elimination of lime and scale buildup associated with steam table holding.
- Increase employee safety with the elimination of burning steam when changing pans.
- Adjustable thermostat with remote control suitable for mounting provides holding temperature flexibility without high steam table temperatures to scorch or burn.

A heated hot food well with an exterior of 18 gauge stainless steel. The hot well is controlled by one (1) adjustable thermostat with a range of 1 through 10. Thermostat includes an ON/OFF control switch and indicator light. The thermostat control is attached to the hot well base by a 30" (762mm) flexible and water tight tether.

The heated well base is available in two depths. The 4-3/8" (111mm) deep unit holds 4" (102mm) deep pans and the 6-3/8" (162mm) deep unit holds 6" (153mm) deep pans. Both units will hold a combination of standard (gastronorm) pan sizes. The hot well includes two (2) full-size pan divider bars and six (6) half/third-size pan divider bars.

☐ MODEL 300-HW: 4-3/8" (111mm) depth, accepts three (3) full-size (gastronorm) pans

☐ MODEL 300-HW/ D6: 6-3/8" (162mm) depth, accepts three (3) full-size (gastronorm) pans

CUL US LISTED COOKING APPLIANCE





PRINTED IN U.S.A.

ADDITIONAL FEATURES & OPTIONS

Also available in 1, 3, 4, and 5 full-size pan capacities.

- Model 100-HW or 100-HW/ D6 One (1) full-size pan*, 12" x 20" x 2-1/2" GN 1/1
- Model 200-HW or 200-HW/ D6 Two (2) full-size pans*, 12" x 20" x 2-1/2" GN 1/1
- Model 400-HW or 400-HW/ D6 Four (4) full-size pans*, 12" x 20" x 2-1/2" GN 1/1
- Model 500-HW or 500-HW/ D6 Five (5) full-size pans*, 12" x 20" x 2-1/2" GN 1/1

*WILL ALSO ACCEPT 4" (100mm) DEEP PANS; D6 UNITS WILL ACCEPT 6" (153mm) DEEP PANS




W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.

PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY



HOT FOOD DROP-IN WELL 300-HW SERIES



L	ELECTRI	CAL				
	VOLTAGE	PHASE	CYCLE/ HZ	AMPS	kW	PLUG CONFIG.
	120	1	50/60	19.6	2.35	nema L5-30p
						30a- 125 V plug
240	at 208	1	50/60	9.2	1.93	NEMA 6-1 5Р
208-240	at 240	1	50/60	10.7	2.57	15a-250v plug
	230	1	50/60	10.2	2.36	bs 1363 plug
						(UK ONLY)

PRODUCT\PAN CAPACITY 36 lb (16 kg) MAXIMUM (BASED ON 4" DEEP PANS) MAX. VOLUME: 22.5 qt (28.5 L) FULL-SIZE PANS*: Three (3) 12" x 20" x 2-1/2" GN 1/1 (325mm x 530mm x 65mm) HALF-SIZE PANS*: Six (6) 12" x 10" x 2-1/2" GN 1/2 (325mm x 265mm x 65mm) THIRD-SIZE PANS*: Nine (9) 12" x 6" x 2-1/2" GN 1/3 (325mm x 176mm x 65mm)

*WILL ALSO ACCEPT 4" (100mm) DEEP PANS; D6 UNITS WILL ACCEPT 6" (153mm) DEEP PANS

HW DIMENSIONS: L x W x D

EXTERIOR:

24-1/8" x 42" x 7-9/16" (613mm x 1066mm x 193mm) WELL DIMENSION:

22-1/16" x 39-11/16" x 4-3/8" (560mm x 1007mm x 111mm) counter cutout dimension:

22-3/8" x 40" (568mm x 1016mm)

CONTROL BOX CUTOUT REQUIRED:

4-1/2" x 5-1/4" (115mm x 137mm)

INSTALLATION REQUIREMENTS

Unit must be installed level and must not be installed in any area where it may be directly affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

Hot well outer walls can reach 200° to 260°F (93° to 127°C). Verify countertop material temperature rating with manufacturer before installing hot well to ensure countertop can withstand heat.

HW/D6	DIMENSIONS: $L \times W \times D$	

EXTERIOR:

24-1/8" x 42" x 9-9/16" (613mm x 1066mm x 193mm) WELL DIMENSION:

22-1/16" x 39-11/16" x 6-3/8" (560mm x 1007mm x 162mm) counter cutout dimension:

22-3/8" x 40" (568mm x 1016mm)

CONTROL BOX CUTOUT REQUIRED:

4-1/2" x 5-1/4" (115mm x 137mm)

CLEARANCE REQUIREMENTS
4" (102mm) from bottom

WEIGHT EST.	300-HW	300-HW/ D6
NET WEIGHT:	92 lb (42 kg)	97 lb (44 kg)
SHIP WEIGHT:	125 lb (57 kg)	130 lb (58 kg)
CRATE DIMENSIONS:	19" x 49" x 31"	
$(H \times W \times D)$	(483mm x 1245mm x 787mm)	

OPTIONS & ACCESSORIES					
PAN DIVIDER BARS					
☐ Full-Size16019					
☐ Half-Size • Third-Size					



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.

PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com