

SR SERIES

high performance component and coaxial speakers

1-inch Kortec® Tweeter

Neodymium Magnets

1½-inch Voice Coil

CATB™ Tweeter Baffle

TwinStage™ Heatsink

VariMount™ Adapters

Metal Grilles

6 Models



 **Boston**
mobile audio

SR SERIES

high performance component and coaxial speakers

HIGH PERFORMANCE COMPONENT AND COAXIAL SPEAKERS

Leading the component drop-in category, Boston SR speakers utilize many key features from our acclaimed Boston Pro speakers, to give them plenty of pure, natural performance—all with minimal distortion and maximum bass. Available in six models plus an accompanying Imaging System, SR speakers are designed specifically for easy installation into a variety of factory locations. SR provides a level of sound quality and installation ease not commonly found at such a popular price point.

PERFORMANCE

- Type-S1, 1-inch Kortec® tweeter, for superb power handling and reliability.
- TwinStage™ heatsink and 1½-inch voice coil for greater power handling.
- Neodymium magnets, for an extraordinary power-to-weight ratio.
- CATB™ (Contoured Asymmetrical Tweeter Baffle) delivers smooth extension and great on- and off-axis response.
- System-specific crossovers with tweeter protection; internal on coaxial models, separable and dockable on SR60 and SR50 components.



INSTALLATION

- Compact neodymium magnets reduce installation clearances and minimize interference problems with window regulators and trunk torque rods.
- VariMount™ adapter rings enable the SR60 and SR65 to fit into nearly any factory 6-inch or 6½-inch location.
- SR60 and SR50 use a separate ¾-inch Kortec® dome tweeter, allowing them to fit into tight OEM locations. Flush, surface and angle mounts allow easy tweeter installation in a variety of applications.
- Mounting depth of 2⅝-inches or less.



| MODEL | TYPE | SIZE | DEPTH | POWER HANDLING | IMPEDANCE | FREQUENCY RESPONSE |
|-------|-----------------|--------|-------|-----------------------|-----------|--------------------|
| SR60 | Component | 6½" | 2⅞" | 85 W RMS / 250 W Peak | 4Ω | 45Hz - 20kHz |
| SR50 | Component | 5¼" | 2⅝" | 85 W RMS / 250 W Peak | 4Ω | 50Hz - 20kHz |
| SR95 | Coaxial | 6 x 9" | 2⅞" | 75 W RMS / 200 W Peak | 4Ω | 35Hz - 20kHz |
| SR80 | Component Plate | 5 x 7" | 2⅝" | 75 W RMS / 200 W Peak | 4Ω | 45Hz - 20kHz |
| SR65 | Coaxial | 6½" | 2⅞" | 75 W RMS / 200 W Peak | 4Ω | 50Hz - 20kHz |
| SR55 | Coaxial | 5¼" | 2⅝" | 75 W RMS / 200 W Peak | 4Ω | 55Hz - 20kHz |

ALSO AVAILABLE:

| | | | | | | |
|------|----------------|----|----|----------------------|----|-------------|
| ISTS | Imaging System | 1" | ¾" | 40 W RMS / 80 W Peak | 8Ω | 8Hz - 20kHz |
|------|----------------|----|----|----------------------|----|-------------|



Boston Acoustics, Inc. 300 Jubilee Drive, Peabody, MA 01960
T: 978-538-5000 F: 978-538-5100 W: bostonacoustics.com

©2009 Boston Acoustics, Inc. Covered by patents issued and pending. All Rights Reserved. TwinStage, VariMount, CATB are trademarks and Boston, Boston Acoustics, the Boston Acoustics logo, and Kortec are registered trademarks of Boston Acoustics, Inc. All specifications are subject to change.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>