

APPLICATION EQUIPMENT

THE TANK™
SPREADER/SPRAYER

XP STAND-ON
SPREADER

XP STAND-ON
SPREADER/SPRAYER

TR20 TURF
RENOVATOR

80-LB. SPREADER

COMMERCIAL
SPRAYERS

FEATURES

SPREADERS FOR
SEEDING, FERTILIZING
OR DE-ICING

25-, 50-, 100-, 200- AND
300-GAL. SPRAYERS

WANDS AND SPRAY
GUNS FOR ANY JOB

PREMIUM KAWASAKI®
OHV ENGINES,
ELECTRIC OR
RECOIL START

1-YEAR LIMITED
COMMERCIAL
WARRANTY†

COMMERCIAL APPLICATION EQUIPMENT



WE MEAN BUSINESS.™



THE TANK™ Spreader/Sprayer shown

A FULL LINE OF PROVEN, RELIABLE EQUIPMENT TO MAKE YOU MORE VALUABLE TO YOUR CUSTOMERS.

How can you make your business more valuable to your customers and more profitable to you? By using our complete line of proven, reliable and highly successful application equipment. Our latest addition, the new XP Stand-On Spreader/Sprayer, features an innovative design with the maneuverability and flexibility you need to be as efficient with your time as possible. Spreaders. Sprayers. Renovators. We're talking rugged, durable equipment that's built to handle any of the toughest jobs and hold up over time. So no matter which piece you're using, you can be assured that you're working with the best equipment available.

THE TANK™ SPREADER/SPRAYER

It's the ultimate machine for spreading and spraying large areas — both in the same pass, if needed. With a 40-gallon tank for spraying and a 125-lb. capacity hopper for spreading. All powered by a 17 HP* Kawasaki® V-Twin engine.

(shown above)

XP STAND-ON SPREADER/SPRAYER



Built on the same platform as the XP Spreader but equipped with dual, independent 5-gallon tanks, as well as boomless spray nozzles mounted to each side of the unit and a spray wand. This 3-in-1 application machine allows you to spread granular products and liquids all at once.

80-LB. SPREADER

The 80-lb. capacity polyethylene hopper and easy rate-adjustment mechanism give you simple but precise material flow control.



TR20 TURF RENOVATOR

Equipped with an 8 HP* Kawasaki® engine and a 35-lb. hopper capacity, the TR20 can be used to dethatch, slice and seed.



COMMERCIAL SPRAYERS

Several options ranging from 25 to 300 gallons to allow you to tackle everything from light-duty work with your

tractor or utility vehicle up to heavy-duty use from the back of your pickup. Most sprayers feature a 5.5 HP* Kawasaki® engine coupled with a hydro pump for increased productivity.

XP STAND-ON SPREADER

Powered by a 6 HP* Kawasaki® engine and hydrostatic drive, the 125-lb. hopper can spread seed or fertilizer. Plus, the sulky-style riding platform and rear-wheel drive give you increased traction and control.



*as rated by engine manufacturer †See your local Cub Cadet Commercial Independent Dealer for warranty information. Download from www.somanuals.com. All Manuals Search And Download.

cubcadetcommercial.com

APPLICATION EQUIPMENT



| | 80-lb. Rotary Spreader | XP Stand-On Spreader | XP Stand-On Spreader/Sprayer | TR20 Turf Renovator | THE TANK™ Spreader/Sprayer |
|------------------------------|---------------------------|---------------------------|--|--|--|
| Engine | - | 6 HP* Kawasaki® | 6 HP* Kawasaki® | 8 HP* Kawasaki® | 17 HP* Kawasaki® |
| Engine series | - | Vertical OHV | Vertical OHV | Horizontal OHV | Vertical OHV |
| Ignition | - | Recoil start | Electric start/recoil | Recoil start | Electric start |
| Cylinder | - | Single | Single | Single | Twin |
| Gear reduction | 5:1 ratio | - | Electric motor | - | - |
| Oil filter | - | Yes | - | - | Yes |
| Hopper/tank width | - | - | 10 gal. total/fender mounted | 20" dethatching/seeding | - |
| Hopper size | 80 lbs. | 125 lbs. | 125 lbs. | 35 lbs. | 125 lbs. |
| Tank size | - | - | Dual 5-gal. tanks/independent | - | 40 gal. |
| Tank shape | Rectangular hopper | Rectangular hopper | Rectangular hopper | Rectangular | Rectangular |
| Strainer | Stainless mesh screen | Stainless mesh screen | Stainless mesh screen | - | - |
| Agitation | Oscillating agitator | Oscillating agitator | Oscillating agitator | - | Triple jet & oscillating agitator |
| Hopper/tank material | Polyethylene | Polyethylene | Polyethylene | Steel | Polyethylene |
| Frame type | Stainless steel | Stainless/welded steel | Stainless/welded steel | Welded steel | Welded steel |
| Frame material | 1" SS tube | 1" SS tube & 7-ga. steel | 1" SS tube & 7-ga. steel | 11-ga. painted steel | Painted steel |
| Drive system | Push | Hydro-Gear™ transmission | Hydro-Gear™ transmission | Hydraulic with chain-driven differential | Kanzaki DUP-10 pumps & White® wheel motors |
| Speeds | - | Fwd: 5 mph, Rev: 3 mph | Fwd: 5 mph, Rev: 3 mph | Fwd: 2 mph, Rev: 1 mph | Fwd: 10 mph, Rev: 4 mph, lock-in application speed |
| Front wheels | 13" x 5.0" - 6" | 13" x 6.5" - 6" | 13" x 6.5" - 6" | 13" x 5.0" - 6" | 13" x 6.5" - 6" |
| Rear wheels | - | 18" x 6.5" - 8" | 18" x 8.5" - 8" | 13" x 5.0" - 6" | 24" x 12" - 12" |
| Pump output | - | - | - | - | 4.8-GPM, 40 psi |
| Pump type | - | - | 12 VDC Flojet™ pump | - | 12 VDC Flojet™ pump |
| Pump pressure | - | - | - | - | - |
| Hose size | - | - | 25-ft. coil hose w/spot wand | - | 25-ft. coil hose |
| Hose material | - | - | PVC | - | PVC |
| Pressure rating (hose) | - | - | 100 psi | - | 100 psi |
| Length x width x height | 48" x 25" x 35" | 56" x 35" x 48" | 56" x 35" x 48" | 31" wide overall | 99" x 57" x 48" |
| Effective spray/spread width | - | 120" | 120"/108" boomless spray | - | 120" |
| Weight | 32 lbs. dry | 340 lbs. dry | 365 lbs. dry | 290 lbs. dry | 1,134 lbs. dry |
| Spray wand/gun | - | - | Spot spray wand & 3 boomless spray nozzles | - | Adj. spot spray wand & 3 section boom 5 nozzle |
| Warranty† | 1-year limited commercial | 1-year limited commercial | 1-year limited commercial | 1-year limited commercial | 1-year limited commercial |

| SPRAYERS | 25 Spot | 50 Poly | 100 Poly | 200 Poly | 300 Poly | 200 Compact |
|-------------------------|----------------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Engine | 12 VDC | 4 HP* Kawasaki® | 5.5 HP* Kawasaki® | 5.5 HP* Kawasaki® | 5.5 HP* Kawasaki® | 5.5 HP* Kawasaki® |
| Engine series | - | Horizontal OHV | Horizontal OHV | Horizontal OHV | Horizontal OHV | Horizontal OHV |
| Ignition | - | Recoil start | Recoil start | Recoil start | Recoil start | Recoil start |
| Cylinder | - | Single | Single | Single | Single | Single |
| Gear reduction | - | 6:1 direct-coupled | 6:1 direct-coupled | 6:1 direct-coupled | 6:1 direct-coupled | 6:1 direct-coupled |
| Tank size | 25 gal. | 50 gal. | 100 gal. | 200 gal. | 300 gal. | 200 gal. |
| Tank shape | •-----Rectangular-----• | | | | | |
| Strainer | In-line SS on inlet side of pump | Stainless steel mesh | Stainless steel mesh | Stainless steel mesh | Stainless steel mesh | Stainless steel mesh |
| Agitation | - | Triple jet spray | Triple jet spray | Triple jet spray | Triple jet spray | Triple jet spray |
| Hopper/tank material | •-----Polyethylene-----• | | | | | |
| Frame type | - | Welded steel | Welded steel | Welded steel | Welded steel | Welded steel |
| Frame material | - | Painted steel | Painted steel | Painted steel | Painted steel | Painted steel |
| Pump output | 4.8-GPM/40 psi | Max. 6-GPM | Max. 9.5-GPM | Max. 9.5-GPM | Max. 9.5-GPM | Max. 9.5-GPM |
| Pump type | Diaphragm | Twin diaphragm | Twin diaphragm | Twin diaphragm | Twin diaphragm | 3-diaphragm |
| Pump pressure | 60 psi | Max. 275 psi | Max. 550 psi | Max. 550 psi | Max. 550 psi | Max. 550 psi |
| Hose reel | - | Hannay® electric | Hannay® electric | Hannay® electric | Hannay® electric | Hannay® electric |
| Hose size | 1/4" i.d. x 25' | 3/8" i.d. x 300' | 1/2" i.d. x 300' | 3/8" i.d. x 400' | 1/2" i.d. x 300' | 1/2" i.d. x 300' |
| Hose material | Flexcoil - PVC | PVC | PVC urethane core | PVC urethane core | PVC urethane core | PVC urethane core |
| Pressure rating (hose) | 100 psi | 300 psi | 800 psi | 800 psi | 800 psi | 800 psi |
| Length x width x height | 30" x 20" x 19" | 54" x 19" x 26" | 48" x 38" x 34" | 65" x 39" x 40" | 88" x 38" x 47" | 62" x 40" x 40" |
| Weight w/o hose & reel | 22 lbs. dry | 125 lbs. | 237 lbs. | 336 lbs. | 422 lbs. | 330 lbs. |
| Weight w/hose & reel | - | 200 lbs. | 371 lbs. | 470 lbs. | 556 lbs. | 454 lbs. |
| Spray wand/gun | Trigger jet w/conejet nozzle | Order as needed | Order as needed | Order as needed | Order as needed | Order as needed |
| Warranty† | 1-year limited commercial | 1-year limited commercial | 1-year limited commercial | 1-year limited commercial | 1-year limited commercial | 1-year limited commercial |

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

*as rated by engine manufacturer † See your local Cub Cadet Commercial Independent Dealer for warranty details. Commercial products are intended for professional use.

773-03687 Printed in U.S.A. 12/08 © 2009 Cub Cadet

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>